



FLUSH MOUNT OR LOW PROFILE MICRO DOME CAMERA

The FS-10 micro dome is a low profile, vandal resistant design that delivers outstanding image quality from the Sony Super HAD 700 TVL CCD. Its design is for applications where infrared or audio are not required. A unique three ring system allows the camera to be partially flush mounted for installations where heavy passenger flow occurs. The FS-10 is tested to MIL SPEC 810-F for operation in tough environmental conditions and can be custom ordered to meet an IP69K rating for high pressure spray and dust ingress.

GATEKEEPER

FS-10 CAMERA

**LOW PROFILE
VANDAL RESISTANT
ABLE TO BE FLUSH MOUNTED**



KEY FEATURES

- Sony CCD 700 TVL
- Meets MIL SPEC 810-F
- No Audio
- No Infrared
- Metal Design
- Unique Flush Mount Design Options
- Vandal Resistant Micro Dome
- Water & Dust Proof
- Built for Extreme Environments

DAY/NIGHT HIGH RESOLUTION CAMERA

GATEKEEPER

Gatekeeper Systems Inc.
301-31127 Wheel Avenue
Abbotsford, BC V2T 6H1
Canada

Gatekeeper Systems USA Inc.
7-200 Rittenhouse Circle East
Bristol, PA 19007
United States

VIDEO

IMAGING SENSOR	Sony Super HAD II, 1/3" CCD
PROCESSOR	Sony
MINIMUM ILLUMINATION	0.3 LUX/F1.2 (no IR)
RESOLUTION	700 TVL
EFFECTIVE PIXELS	976 (H) x 494 (V)
VIDEO OUTPUT	1.0V P-P/75 Ω, NTSC
S/N RATIO	≥ 50db
ELECTRONIC SHUTTER	Auto
GAMMA CORRECTION	0.45
AGC	Auto
BLC	Auto
WHITE BALANCE	Auto

AUDIO

Not available

IR

Not available

AVAILABLE LENSES

1.7mm (fisheye), 2.9mm and 3.6mm

VOLTAGE

POWER CONSUMPTION

12v nominal
≤1W with IR On

PHYSICAL

EXTERIOR DIMENSIONS

(Ø x H) 2.9" x 1.4" (74mm x 35mm)

WEIGHT

.3 lbs (136g)

OPERATING TEMPERATURE

-22°F to +140°F (-30°C to +60°C)

OPERATING HUMIDITY

Under 90% (Non-Condensing)

ADAPTOR PLATES

0° (flush mount)
10°, 15°, 25°

