



## VERSATILE DOME CAMERA

The S370 camera utilizes Sony imaging technology to deliver superior video quality in both day and night lighting conditions.

A full-metal, vandal resistant design protects the lens and circuitry for long lasting performance.

Its unique 3D gimbal allows the base of the camera to be mounted in any orientation such as curved bus ceilings, enabling the camera to be adjusted so the image is correctly oriented.

# GATEKEEPER

## S370 CAMERA

**FULLY ADJUSTIBLE  
VANDAL RESISTANT  
MOUNT IN ANY ORIENTATION**



### KEY FEATURES

- Integrated audio
- 24 LED's for night vision
- 90 degree aiming
- Vandal resistant full-metal design
- Total-Seal design to resist water spray
- Concealed connectors for long term reliability

# DAY/NIGHT HIGH RESOLUTION CAMERA

# GATEKEEPER

Gatekeeper Systems Inc.  
301-31127 Wheel Avenue  
Abbotsford, BC V2T 6H1  
Canada

Gatekeeper Systems USA Inc.  
7-200 Rittenhouse Circle East  
Bristol, PA 19007  
United States

## VIDEO

IMAGING SENSOR	1/3" Sony 1.27 Mega Pixel CMOS
PROCESSOR	Sony
MINIMUM ILLUMINATION	0.1LUX/F1.2 (no IR), 0.0 LUX (IR On)
VIDEO FORMAT	NTSC
RESOLUTION	800 TVL
EFFECTIVE PIXELS	976 (H) x 494 (V) 1.0V P-P/75Ω, NTSC
VIDEO OUTPUT	≥ 50db (AGC Off)
S/N RATIO	1/60 to 1/100,000, auto
ELECTRONIC SHUTTER	0.45
GAMMA CORRECTION	Auto
AGC	Auto
BLC	Auto
WHITE BALANCE	Auto

## AUDIO

Yes - integrated mic and line driver

## IR

24 LED's (850nm) with integrated on/off sensor

## HOUSING

Gatekeepers S3 camera housing

## AVAILABLE LENSES

2.8mm, 3.6mm, 4.2mm, and 6.0 mm

## POWER

VOLTAGE	12v nominal
POWER CONSUMPTION	≤3W WITH IR ON

## PHYSICAL

EXTERIOR DIMENSIONS	2.8" H x 3.6" base diameter 71.0mm H x 91.0mm base diameter
WEIGHT	.5 lbs (215g)
OPERATING TEMPERATURE	-22°F to +131°F (-30°C to +55°C)
OPERATING HUMIDITY	Under 90% (Non-Condensing)



REAR VIEW MOUNTING OPTION



STAIRWELL VIEW MOUNTING OPTION



SIDE MOUNTING OPTION