

INTELLIGENT TEMPERATURE SENSING SYSTEMS (ITSS™)

Gatekeeper's Intelligent Temperature Sensing System includes a stand-alone health monitoring panel that measures the body temperature of individuals entering a transportation vehicle or building. Thermal cameras, artificial intelligence and video analytics are used to rapidly and accurately measure body temperature. The ITSS panel can be configured to provide an audio warning if a mask is or is not detected. The compact panel is easy to install and helps ensure a healthier environment for passengers, employees and organizations.

GATEKEEPER

HEALTH MONITORING PANEL

AI DRIVEN, FACIAL CAPTURE HIGHLY ACCURATE



KEY SPECIFICATIONS

- Contactless operation
- Artificial Intelligence
- Fast measurement
- Captures temperature of riders within 2 feet
- Visual and audible alarms triggered on configurable high temperature limits
- Audio warning if a mask is not detected
- Stand-alone system does not require DVR , quick and easy installation

RAPID READING- LESS THAN ONE SECOND

GATEKEEPER

Gatekeeper Systems Inc. 301-31127 Wheel Avenue Abbotsford, BC V2T 6H1 Canada Gatekeeper Systems USA Inc. 200 Rittenhouse Circle Suite 7E Bristol, PA 19007 USA

PANEL SPECIFICATIONS

TEMPERATURE MEASUREMENT

TEMPERATURE DETECTION RANGE 95°F to 107°F (35° to 42°C)

ACCURACY $\pm 0.6^{\circ} F (\pm 0.5^{\circ} C)$

DETECTION RANGE ≤23 - 60 inch (≤0.6 - 1.5 meter)

ALARM THRESHOLD Configurable, preconfigured to 99.14°F (37.3°C)

RESPONSE TIME <300 mS

FACIAL CAPTURE

DETECTION MODE Single target capture – driven by Artificial Intelligence

CAPTURE DETECTION ACCURACY 99.9%

MONITOR

 SCREEN SIZE
 7 inches

 SCREEN LUMINANCE
 450 cd/m2

 ASPECT RATIO
 16:9

 RESOLUTION
 600* 1024

POWER

POWER INPUT9-36V DCPOWER CONSUMPTION9W typical

TRIGGER Vehicle accessory or ignition with adjustable power down delay

OPTIONAL 115V power kit

ENVIRONMENTAL

IP RATING IP30

OPERATING TEMPERATURE32°F to 122°F (0°C - 50°C)STORAGE TEMPERATURE-22°F to 167°F (-30°C - 75°C)OPERATING HUMIDITY15% - 95% non condensingSTORAGE HUMIDITY15% - 95% non condensing

SHOCK AND VIBRATION MIL STD-810F

PHYSICAL

DIMENSION 10.9" x 4.9" x 1.2" (267mm x 125mm x 30mm)

WEIGHT 7oz (200g)

