

1080P WINDSHIELD HD CAMERA

Built rugged, the TW202 IP v3 camera is a high definition IP camera designed to mount directly on the front windshield of a vehicle using 3M adhesive. The metal housing makes the camera vandal resistant and when installed, virtually immune to tampering. This design prevents passengers and drivers from changing the cameras field of view. The TW202 IP v3 is a 1080p camera that is compact in size and light weight. The camera is a day/night camera and produces exceptional picture quality in any light.

GATEKEEPER

TW202 IP v3 CAMERA

WINDSHIELD MOUNTED WIDE DYNAMIC RANGE 1080P CAMERA



KEY FEATURES

- Easy mounting using 3M adhesive
- RJ45 Network Connection
- Vandal resistant
- Compatible with all current Gatekeeper DVRs
- Compatible with windshield rake between 19° and 90°
- USA National Defense Authorization Act (NDAA) compliant
- Dust & water spray resistant (IP53)
- 5 Year Warranty

WINDSHIELD MOUNTED 1080P CAMERA

GATEKEEPER

Gatekeeper Systems Inc. 301-31127 Wheel Avenue Abbotsford, BC V2T 6H1 Canada Gatekeeper Systems USA Inc. 7-200 Rittenhouse Circle East Bristol, PA 19007 United States

VIDEO

IMAGING SENSOR2 MP 1/2.8" CMOSMINIMUM ILLUMINATION0.05 LUX (Color Illumination), F1.2

RESOLUTION1080p, 720p, D1EFFECTIVE PIXELS2.43M effective pixels

WIDE DYNAMIC RANGE

DATA STREAM

COMPRESSION

Yes - Wide Dynamic Range ≥80db

ONFIV Profile S, v2.4

H.264 / H.265

BIT RATE 512Kbps to 8Mbps
DUAL STREAM Main:

1080p (1920 x 1080) 720p (1280 x 720)

ELECTRONIC SHUTTER 1/30 Second - 1/10,000 Second

GAMMA CORRECTION 0.45
AGC Auto
WHITE BALANCE Auto

HOUSING

CABLING CONNECTION

AVAILABLE LENSES

APERTURE

POWER

VOLTAGE CONSUMPTION

PHYSICAL

EXTERIOR DIMENSIONS

WEIGHT
IP RATING
OPERATING TEMPERATURE
OPERATING HUMIDITY

AUDIO

AUDIO OPTION AUDIO FORMAT Gatekeeper's TW camera housing

13.8" (35cm) long: RJ-45 Female

2.8mm, 4mm, 8mm

M12 Fixed Aperture F1.8

POE12 (DC12V Nominal)

4.8" (L) x 3.0" (H) x 1.5" (W)

121.6mm (L) x 75mm (H) x 39mm (W)

1.1lbs (500g) IP53

-40°F to +158°F (-40°C to +70°C)

Under 90% (Non-Condensing)

Built-in mic G711a/G711u/G726



View of camera mounted from inside



